

YELOfon[®] HD10+ System

UK's No.1 High Performance Under Screed Resilient Layer



Over 12,500,000m² successfully installed

Product Information

YELOfon[®] HD10+ is an acclaimed resilient layer system that carries 3 proprietary Robust Details: E-FC-5, 17 & 18. The System is lightweight, easy to install and delivers unrivalled acoustic performance when used to isolate a floating screed from a structural concrete floor.

Product Benefits

- Superior impact sound deadening properties
- Suitable for all types of concrete floors and screeds
- Supplied as a kit with 1 x E-strip and 2 x J-strips included
- Lightweight, easy to handle and install rolls
- Works in conjunction with underfloor heating

YELOfon[®] HD10+ System

		HD10+	E-strip	J-strip
Product description	-	Surebond faced resilient layer	Perimeter edge strip	Acoustic jointing tape
Thickness	mm	10	7	2.5
Roll dimensions	-	1.5m x 33.33m	200mm x 33.33m	75mm x 40m
Coverage	m ²	50	N/A	N/A
Weight	kg/roll	18.0	1.75	0.54
Thermal conductivity	W/mK	0.045	0.045	0.037
Long term water absorption	%	<5 (after 28 days)	<5 (after 28 days)	<5 (after 28 days)

Third Party Accreditation and Approvals



Environmental Credentials

