



Declaration of Performance
DOP Number: L/MirrorWrap/001

1. Unique identification code of the product:

Novia MirrorWrap W1

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Underlays for discontinuous roofing according to EN 13859-1 and walls according to EN 13859-2

3. Name and contact address of the manufacturer:

Novia Ltd, Unit 3 Trilogy
Eurolink V Industrial Park
Sittingbourne, Kent
ME10 3NH

4. System of assessment and verification of constancy of performance of the construction product:

System 3

5. Notified body:

Technický a skúšobný ústav stavebný, n.o., Notified body 1301 performed the initial type test according to EN 13859-1 and EN 13859-2

6. Declared Performance:

Essential Characteristics	Specified Value	Unit	Test standard
Tensile strength MD CD	200 (-50/+150) 110 (-10/+70)	N/50mm	EN 12311-1
Maximum elongation at tensile strength MD CD	75 (-35/+45) 90 (-50/+50)	%	EN 12311-1
Nail Tear resistance MD CD	80 (-5/+40) 110 (-10/+55)	N	EN 12310-1
Water vapour transmission properties SD	0.08 (-0.05/+0.02)	m	EN ISO 12572
Resistance to water penetration	W1		EN 1928
Flexibility at low temperature	-40	°C	EN 1109
Flame resistance*	E*		EN 13501-1
DURABILTY AFTER ARTIFICIAL AGEING TO			
Resistance to water penetration	W1		EN 1928
Tensile strength MD CD	190 (-60/+80) 95 (-25/+55)	N/50mm	EN 12311-1
Maximum elongation at tensile strength MD CD	55 (-30/+45) 65 (-40/+55)	%	EN 12311-1

*Tested on chipboard according to EN 13238

7. The performance of the product according to product (1) corresponds to the declared performances in section 6.

.....
Adrian Chisholm, Managing Director
Novia Limited, Sittingbourne, Kent, UK

...01-08-2024...

Date